

金属减缩环
Metal Reducer




M / PG

CE ROHS

材质: 镀镍黄铜
防水圈: 丁腈橡胶、硅橡胶
防水等级: IP54
工作温度: 静态: -40°C到 100°C, 短时间达 120°C

Material: Nickel-plated brass
O-Ring: NBR, Silicone rubber
Protection degree: IP54
Temperature: Static state: -40°C to 100°C
short time to 120°C



六角
Hexagonal



圆形
Round

规格 Item	螺纹 Thread		螺纹长度 GL	高度 H Joint Length	扳手径 φ Spanner size	产品编号 Code
	Outer	Inner				
M16-M12	M16 X 1.5	M12 X 1.5	6	9	18	HX-REM16-M12
M20-M16	M20 X 1.5	M16 X 1.5	6.5	9.5	22	HX-REM20-M16
M25-M20	M25 X 1.5	M20 X 1.5	7.5	10.5	27	HX-REM25-M20
M32-M25	M32 X 1.5	M25 X 1.5	8	11.5	35	HX-REM32-M25
M40-M32	M40 X 1.5	M32 X 1.5	9	12.5	45	HX-REM40-M32
M50-M40	M50 X 1.5	M40 X 1.5	10	14	55	HX-REM50-M40
M63-M50	M63 X 1.5	M50 X 1.5	10	14	68	HX-REM63-M50
PG9-PG7	PG9	PG7	6	9	18	HX-REPG9-PG7
PG11-PG9	PG11	PG9	6.5	9.5	20	HX-REPG11-PG9
PG13.5-PG11	PG13.5	PG11	6.5	9.5	22	HX-REPG13.5-PG11
PG16-PG13.5	PG16	PG13.5	6.5	9.5	24	HX-REPG16-PG13.5
PG21-PG16	PG21	PG16	7.5	10.5	30	HX-REPG21-PG16
PG29-PG21	PG29	PG21	8	11.5	40	HX-REPG29-PG21
PG36-PG29	PG36	PG29	9	12.5	50	HX-REPG36-PG29
PG42-PG36	PG42	PG36	10	14	57	HX-REPG42-PG36
PG48-PG42	PG48	PG42	10	14	64	HX-REPG48-PG42



其他附件
Other Matched Accessories

金属软管

Metal Flexible Pipe




PM / BM

CE ROHS

材质: 热浸镀锌钢板及特殊绝缘处理
 外层: PVC(黑色抗紫外线, 防老化)
 产品认证: 欧洲 CE, 欧洲环保 RoHS
 防火等级: UL94V-0, 低烟无毒
 颜色种类: 黑色或灰色
 使用方法: 先将电线穿入管内, 再配合金属软管固定头即可

Material: Hot dip galvanized steel plate and special insulation treatment
 Out Material: PVC(black anti-ultraviolet, anti-aging)
 Product certification: European CE, European environmental protection RoHS
 Fire rating: UL94v-0, low smoke non-toxic
 Color: black or grey
 Working temperature: - 30 °C to + 85 °C, instantaneous heat resistant up to 100 °C
 Usage: Put the wire into the tube, then tie the metal hose to the head



规格参数 单位: mm

型号 Item No.		规格 Trade Sizes		内径 d Inner Diameter	外径 D Outer Diameter	弯曲半径 Bending Radius mm±10%	包装 M Packing
黑色 Black	灰色 Gray	公制 M	英制 BSP				
HX-PM-01B	HX-PM-01G	6	3/16"	6.0±0.3	9.2±0.5	40	100M
HX-PM-02B	HX-PM-02G	8	5/16"	8.0±0.3	11.8±0.5	45	100M
HX-PM-03B	HX-PM-03G	10	1/4"	10.0±0.3	14.5±0.5	55	100M
HX-PM-04B	HX-PM-04G	13	3/8"	12.5±0.3	16.8±0.5	65	100M
HX-PM-05B	HX-PM-05G	16	1/2"	15.5±0.3	20.2±0.5	85	100M
HX-PM-06B	HX-PM-06G	20	3/4"	20.0±0.3	25.0±0.5	100	50M
HX-PM-08B	HX-PM-08G	25	1"	25.0±0.3	30.7±0.5	120	50M
HX-PM-10B	HX-PM-10G	32	1 1/4"	32.0±0.3	38.6±0.5	150	25M
HX-PM-12B	HX-PM-12G	38	1 1/2"	38.0±1.0	44.6±1.0	180	25M
HX-PM-16B	HX-PM-16G	51	2"	51.0±1.0	59.0±1.0	220	10M
HX-PM-20B	HX-PM-20G	64	2 1/2"	64.0±1.5	73.5±1.5	310	10M
HX-PM-24B	HX-PM-24G	75	3"	75.0±2.0	83.5±2.0	350	10M
HX-PM-32B	HX-PM-32G	100	4"	100.0±3.0	109.5±3.0	410	10M
HX-PM-36B	HX-PM-36G	125	5"	125.0±3.0	135.5±3.0	460	5M
HX-PM-38B	HX-PM-38G	150	6"	150.0±4.0	160.5±4.0	500	5M



金属软管系列 Metal Hose Fitting Series